

# Rondissade

Your property and access, our challenge

VERTICAL BAR FENCING



## Rondissade: safety with a luxury appearance

### Beautiful

Characteristic of Rondissade chain link fencing are the vertical, round bars that run through the horizontal beams. Many of our customers find this version aesthetically appealing. The blind connection between posts and bar panels further strengthens this. Black plastic covers on the posts complete the picture.

### Robust and maintenance-free

In order to firmly anchor the Rondissade chain link fencing for years, B&G drives the posts deep into the soil. The blind connection between posts and bar panels promote safety

and prevent unwanted disassembly. Because this fencing also meets the highest quality standards, customers can count on a maintenance-free fencing for years to come.

### Application

Rondissade vertical bar fencing on sites where a secure enclosure with a luxury appearance is desired. For example:

- business parks
- industrial sites
- schools
- sports grounds



Security starts outside



**GARDA**  
SIKRING

# Rondissade

## TECHNICAL SPECIFICATIONS

Rondissade type	100	125	150	180	200	250
Heights	1000	1250	1500	1800	2000	2500
<b>Posts</b>						
Posts	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60
Driving depth	900	900	900	900	900	900
<b>Bar panel</b>						
Bars (round mm)	25	25	25	25	25	25
Bar tops	recht	recht	schuin	schuin	schuin	schuin
Beams	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25
<b>Bank panel</b>						
Straight 90 degrees	-	-	yes	yes	yes	yes
Sloping 60 degrees	-	-	yes	yes	yes	yes
Width	-	-	1000	1000	1000	1000
<b>Sloping panel (option)</b>	<b>yes</b>	<b>yes</b>	<b>yes</b>	<b>yes</b>	<b>yes</b>	<b>yes</b>

Dimensions in ca. mm.

### Version

#### Construction

#### Bar panel

- beams: steel hollow section
- bars: round 25 mm, bevelled from a 1500 mm height and up; centre-to-centre distance: 150 mm

#### Posts

- square hollow section
- finish: black plastic cover

#### Surface treatment

- galvanized
- galvanized, then powder coated according to the Duplex-system

#### Standard colours

- hot-dip galvanized
- hot-dip galvanized, then powder coated according to the Duplex-system

### Options

- shield

#### Anti-climb protection

- barbed wire (2 or 3 rows)
- razor blade tape (2 or 3 rows)
- rotating pointed segment (1 row, approx. 60 mm or 120 mm)
- rotating pointed combs (single or double row)
- current-carrying detection

### Assembly

#### Posts

- standard: driving depth of approx. 900 mm
- in case of insufficiently compacted soil: assembly of a profiled anchor plate on the sunken part of the post
- in case of a concrete floor: assembly with welded base plates
- centre-to-centre distance: 3005 mm

#### Bar panels

- blind connection with posts by means of plastic plugs and M8 end-to-end connections

#### Cope with height differences by:

- slope panels (top beams run parallel to the slope)
- assembly in a cascading way (top beams run horizontally)

**B&G Fencing**  
 Industrieweg 187a  
 NL- 5683 CC Best  
 PO Box 66  
 NL-5680 AB Best

Tel.: +31 499 363 666  
 Fax: +31 499 399 945  
 info@bgfencing.com

**B&G Belgique**  
 Wayenborgstraat 11  
 2800 Mechelen

Tel.: (015) 202 400  
 Fax: (015) 206 200  
 info@bgcloture.be



www.bgfencing.com



**GARDA**  
 SIKRING