



Barricade

'functional and timeless'

applications

industrial sites
office parks
transport companies

series

Barricade
Educade
Palissade
Rondissade

With the Barricade chain link fencing B&G has a functional and timeless classic in its range. The sleek and modern looking fence is applicable on a wide variety of sites. Characteristic are the round bars which are placed between the beams. Also striking is the dragon tail. We apply it standard on the Barricade fencing of 1.5 meter and up as anti-climb protection.

Firmly anchored

In order to firmly anchor the Barricade fencing for years, B&G drives the posts deep into the soil. The blind connections between posts and bar panels further promote safety. They are vandal-resistant and prevent unwanted disassembly.

Application

Barricade vertical bar fencing is very suitable for sites where sleek, sustainable fencing is desired. We often apply it around:

- business parks
- industrial sites
- schools
- sports grounds



Changes in construction and specifications reserved. Version BA-0218

Barricade

TECHNISCHE SPECIFICATIES

Barricade type	100	125	150	180	200	250
Hoogte hekwerk	1000	1250	1500	1800	2000	2500
Standers						
Staander	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60	60 x 60
Inheidiepte ca.	900	900	900	900	900	900
Spijlenvak						
Spijlen	rond 25	rond 25	rond 25	rond 25	rond 25	rond 25
Puntenkam	nee	nee	ja	ja	ja	ja
Boven- en onderligger	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25	50 x 25
Slootvak						
Recht 90 graden	-	-	ja	ja	ja	ja
Schuin 60 graden	-	-	ja	ja	ja	ja
Breedte	-	-	1000	1000	1000	1000
Puntenkam rondom	-	-	ja	ja	ja	ja
Taludvak (optie)	ja	ja	ja	ja	ja	ja

Version

Bar panel

- beams: steel hollow section
- bars: round, centre-to-centre distance: 150 mm
- with dragon tail from a 1500 mm height or up: 35 mm sharp points

Posts

- square hollow section
- finish: black plastic cover

Surface treatment

- galvanized
- galvanized, then powder coated according to the Duplex-system

Standard colours

- RAL 6009 (pine green)
- RAL 6005 (moss green)
- RAL 9005 (black)

Other RAL-colours are available upon request.

Options

- shield

Anti-climb protection

- barbed wire (2 or 3 rows)
- razor blade tape (2 or 3 rows)
- rotating pointed segment (1 row, approx. 60 mm or 120 mm)
- rotating pointed combs (single or double row)
- current-carrying detection

Assembly

Posts

- standard: driving depth of approx. 900 mm
- centre-to-centre distance: 2315 mm
- in case of insufficiently compacted soil: assembly of a profiled anchor plate on the sunken part of the post
- in case of a concrete floor: assembly with welded base plates

Bar panels

- blind connection with posts by means of plastic plugs and M8 end-to-end connections

Cope with height differences by:

- slope panels (top beams run parallel to the slope)
- assembly in a cascading way (top beams run horizontally)

B&G Fencing

Industrieweg 187a
5683 CC Best
Postbus 66
5680 AB Best

Tel.: (0499) 363 666

Fax: (0499) 399 945

info@bghekwk.nl

België

Wayenborgstraat 11
2800 Mechelen

Tel.: (015) 202 400

Fax: (015) 206 200

info@bghekwk.be

