

CERTIFIKAT

EC Certificate of Conformity No. 0402 - CPD - SC0637-10

In compliance with Council Directive 89/106/EEC of 21 December 1988 on the approximation of laws. regulations and administrative provisions of the Member States relating to construction products (the Construction Products Directive or CPD - implemented in Swedish law by BVL), as later amended, it has been stated that the construction product

Road restraint system – Safety barrier as specified in appendix to this certificate

Product name: Safeline, one- and doublesided

placed on the market by

VIK Ørsta AS Postboks 193, NO-6150 Ørsta Norway

and produced in the factories in

Hovden and Ura, NO-6150 Ørsta Norway and Vik, NO-6893 Vik i Sogn, Norway

is submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the notified body

No. 0402 - SP Technical Research Institute of Sweden

has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

> This certificate attests that all provisions concerning the attestation of conformity and the performances described in Annex ZA of the standard

EN 1317-5:2007/A1:2008

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on 16th February 2011 and remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly or at the latest until 16th February 2016. This is issue No. 1.

Borås 16th February 2011

SP Technical Research Institute of Sweden Certification - Notified Body No. 0402

Lennart Månsson Certification Manager Klas Johansson Certification Officer



Appendix to CERTIFIKAT 0402 - CPD - SC0637-10

dated 16th February 2011

Road restraint system - Safety barrier **Guardrail Safeline** according to EN 1317-5:2007/A1:2008

Classification according to EN 1317-2:1998/A1:2006

Product	Containment level	Impact severity level	Working width [m]	Dynamic deflection [m]
Safeline one-sided guardrail CC 3 m	N2	А	1.7 (W5)	1.6
Safeline double-sided guardrail CC 3 m	N2	А	1.5 (W5)	1.2

Product description and configuration

Product	Description		
Safeline, one-sided and double-sided guardrail CC 3 m	Steel tube rail Steel post distance Post length Post embedment min.	3000 mm 1700 mm 950 mm	

SP Technical Research Institute of Sweden