



# CERTIFIKAT

## Certificate of constancy of performance

**0402 - CPR - SC0666-13**

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

### Road restraint system – Safety barrier

as specified in appendix to this certificate

**Product name: VIK SVV1 and VIK SVV2**

placed on the market by

**VIK Ørsta AS**

**Postboks 193, NO-6150 Ørsta**

**Norway**

and produced in the factory/ies

**name and address as above, and according to separate list**

(factory, company and address documented in file at SP)

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

**EN 1317-5:2007/A1:2008**

under system 1 are applied and that

**the products fulfil all the prescribed requirements set out in Appendix.**

This certificate was first issued on 2013-10-22 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Borås 2013-10-22

**SP Technical Research Institute of Sweden**

**Certification, Notified Body No. 0402**



Lennart Aronsson  
Product Certification Manager



Susanne Hansson  
Certification Officer

### Road restraint system – Safety barrier

#### VIK SVV1, VIK SVV2 according to EN 1317-5:2007/A1:2008

#### Classification according to EN 1317-5:2007+A1:2008 (EN 1317-2:1998)

Product	Containment level	Impact severity level	Working width [m]	Dynamic deflection [m]
VIK SVV1* CC 2 m	H2	B	W4 (1.2)	0.8
VIK SVV2* CC 2 m	H2	B	W1 (0.6)	0.4

\*ITT

#### Classification according to EN 1317-5:2007+A1:2008

Product	Durability
VIK SVV1, SVV2 CC 2 m	Hot dip galvanized, acc. to EN ISO 1461

#### Product description and configuration

Product	Description
VIK SVV1, SVV2 CC 2 m	<p>Barrier height above road surface: 1.20 m</p> <p>Longitudinal beam: W-profile (A-profile) with U-section top rail</p> <p>Backside beam SVV1: U section</p> <p>Backside beam SVV2: W section</p> <p>Beam height above road surface: 0.60 m (centre of beam)</p> <p>Post distance: 2.0 m</p> <p>Steel post length: 1005 mm (post welded to base plate)</p> <p>Edge beam height: 150 mm</p>