



CERTIFIKAT

Certificate of constancy of performance

0402 - CPR - SC0667-13

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011*
(the Construction Products Regulation or CPR), this certificate applies to the construction product

Road restraint system – Safety barrier

as specified in appendix to this certificate

Product name: VIK-P-CC 4 m

placed on the market by

VIK Ørsta AS

Postboks 193, NO-6150 Ørsta

Norway

and produced in the factory

name and address as above, and according to separate list

(factory, company and address documented in file at SP)

This certificate attests that all provisions concerning the assessment and verification
of constancy of performance and the performances described in Annex ZA of the standard

EN 1317-5:2007/A1:2008

under system 1 are applied and that

the products fulfil all the prescribed requirements set out in Appendix.

This certificate was first issued on 2013-10-22 and will remain valid as long as the test methods
and/or factory production control requirements included in the harmonised standard,
used to assess the performance of the declared characteristics, do not change, and the product,
and the manufacturing conditions in the plant are not modified significantly.

Borås 2013-10-22

SP Technical Research Institute of Sweden

Certification, Notified Body No. 0402

Lennart Aronsson
Product Certification Manager

Susanne Hansson
Certification Officer

Road restraint system – Safety barrier

VIK-P-CC 4m

according to EN 1317-5:2007/A1:2008

Classification according to EN 1317-5:2007+A1:2008 (EN 1317-2:1998)

Product	Containment level	Impact severity level	Working width [m]	Dynamic deflection [m]
VIK-P-CC 4m*	N2	A	W7 (2.3)	2.3

*ITT

Classification according to EN 1317-5:2007+A1:2008

Product	Durability
VIK-P-CC 4m	Hot dip galvanized, acc. to EN ISO 1461

Product description and configuration

Product	Description
VIK-P-CC 4m	Longitudinal beam: W-profile (A-profile)
	Height above road surface: 0.60 m (centre of W-profile/A-profile)
	Post distance: 4.0 m
	Post embedment: min 1200 mm (in soil)
	Plastic post length: 2000 mm (Borealis HDTE development grade TL2000.10)
	Dimensions of post diameter: 140 mm thickness: 14 mm